

Technical Specifications

KRD13 Series High Energy
Shock Test System



KRD13 series high energy shock test system is specially designed to meet the requirements of military industry and home appliances. The system adopts the principle of pneumatic energy storage expansion. By adjusting the inflation pressure, various high-level acceleration tests can be easily implemented in a short stroke.

For the classic drop test, it's equipped with the corresponding shock amplifier to complete drop test.

- **Windows-based stable control system**, full-automatic remote-control interface
- **Pneumatic cylinder driving** with advantages of large driving force, short accelerating stroke, low cost and pollution free.
- **Automatic control of lifting height** with high accuracy and good repeatability
- **Adopts the high strength and hardness cast aluminum table**, which has high first-order resonance frequency, featured with low noise and no clutter
- **The most reliable double-brake system**: effectively avoids secondary rebound collisions, more securely positioning the table, and more reliably guarantees the safety of the operator.
- **Easy installation**: the device comes with a base, due to short driving stroke of the pneumatic cylinder, the footprint is small.

Technical Specifications

Model		KRD13 – 50	KRD13 – 100	KRD13 – 200	KRD13 – 500	KRD13 – 800	KRD13 – 1000	KRD13-2000
Parameters								
Rated Load (kg)		50	100	200	500	800	1000	2000
Table Size (mm)		500×500	600×600	800×800	1000×1000	1200×1200	1500×1500	2000×2000
Peak Acc. (G)	Half-Sine	10~1500		10-1000	10-500	10-400	10-300	10-200
	Post-Peak Sawtooth	10~200		10~100				10-50
	Trapezoid	15-200	15-200	15-100	15-100	15-60	15-50	30-50
Pulse Duration (ms)	Half-Sine	2 ~ 60	2 ~ 60	3 ~ 60	4 ~ 60	5 ~ 60	6 ~ 60	8 ~ 60
	Post-Peak Sawtooth	3 ~ 18			6 ~ 18			
	Trapezoid	3 ~ 18		6 ~ 18				
Bump Waveform		Half Sine Waveform						
Shock Peak Acceleration (g)		5 ~ 100						
Shock Pulse Duration(ms)		3 ~ 30						
Bump Rate (Times/Min)		10-120						
Overall Dimension (mm)		1200×1200×1 500	1200×1200×1 500	1200×1200×1 500	1300×1300×1 600	1500×1500×1 700	1600×1600×1 800	2000×2000×1 900
Weight (kg)		3000	3200	3400	4000	5000	6000	8000

Installation Condition	Environment	Temperature range 0 ~ 40°C; Humidity ≤ 80%, non-condense
	Power	AC220V±10%, 50Hz
	Air source	≤1MPa
	Floor	Foundation-free, the cement floor shall be leveled and the working distance of 800 ~ 1000mm shall be reserved around the equipment
Standards	MIL-STD-810F IEC68-2-27 UN38.3 IEC62281 IEC62133-2 UL2054 IEEE1625 SAEJ2929 IEC62660-2 ISO12405-3 UL2580	

Note: The parameters in the table are for reference only, and the parameters agreed upon by the supplier and the buyer shall prevail.